

Clarification

SIHA® Gelatin Liquid



SIHA Gelatin Liquid fining agent from Eaton's Begerow Product Line is a stable, 20% aqueous gelatin solution for treating grape mash and grape must.

Because it is easy to use, SIHA Gelatin Liquid fining agent is particularly recommended for the fining of mashes and musts and can usually be used without preliminary tests, based on empirical values. For the fining of wine and fruit juices a preliminary test should be carried out to determine the individual requirements and optimize the fining effect.

Preliminary Test

Pour 3.38 fl oz (100 ml) of beverage into a measuring cylinder and add diluted SIHA Gelatin Liquid fining agent (dilution ratio 20:1; 0.17 fl oz (5 ml) gelatin for 3.38 fl oz (100 ml) of water at 68 °F (20 °C)) according to the following table:

fl oz (ml) diluted gelatin solution (for 3.38 fl oz (100 ml) of beverage)	Corresponds to an addition to the beverage of
0.017 (0.5)	3.2 fl oz/100 gal (25 ml/hl) liquid gelatin = 0.42 lb/1,000 gal (5 g/hl dry gelatin)
0.03 (1.0)	6.4 fl oz/100 gal (50 ml/hl) liquid gelatin = 0.83 lb/1,000 gal (10 g/hl dry gelatin)
0.06 (2.0)	12.8 fl oz/100 gal (100 ml/hl) liquid gelatin = 1.67 lb/1,000 gal (20 g/hl dry gelatin)
0.09 (3.0)	19.2 fl oz/100 gal (150 ml/hl) liquid gelatin = 2.5 lb /1,000 gal (30 g/hl dry gelatin)

Add the exact quantity of diluted gelatin solution with a pipette and mix the preparation thoroughly by shaking the sealed cylinder. If there is no precipitation, flocculation can be triggered by adding BEVASIL® 30 silica sol fining agent (1 – 4 times the gelatin quantity).

Dilute BEVASIL 30 silica sol with a ratio of 1:10 (0.34 fl oz (10 ml) BEVASIL 30 silica sol fining agent solution for 3.38 fl oz (100 ml) of water at 68 °F (20 °C)).

A preliminary test can be done using following quantities:

Gelatin fining in the beverage fl oz/100 gal (ml/hl)	BEVASIL 30 silica sol fl oz/100 gal (ml/hl) of beverage	BEVASIL 30 silica sol, diluted fl oz/gal (ml/100 ml)
3.2 (25)	1.92 – 6.4 (15 – 50)	0.19 – 0.64 (0.15 – 0.5)
6.4 (50)	3.84 – 12.8 (30 – 100)	0.38 – 1.28 (0.3 – 1.0)
12.8 (100)	7.68 – 25.6 (60 – 200)	0.77 – 2.56 (0.6 – 2.0)
19.2 (150)	11.52 – 38.4 (90 – 300)	1.15 – 3.84 (0.9 – 3.0)

The fining effect sets in after several hours of reaction time. Please bear in mind that thanks to better mixing and the somewhat higher temperatures involved, the fining procedure will normally be completed more rapidly than in practical use.

Dosages

For the application of SIHA Gelatin Liquid fining agent without a preliminary test the following dosages can be used for guidance. Depending on the product, dosage required in practice may, however, vary considerably.

Application	SIHA Gelatin Liquid
Mash fining	
Healthy grapes	3.84 – 8.96 fl oz/100 gal (30 – 70 ml/hl = 6 – 14 g/hl)
Partially rotten grapes	9.6 – 12.8 fl oz/100 gal (75 – 100 ml/hl = 15 – 20 g/hl)
Heavily rotten grapes/frost damaged grapes	12.8 – 25.6 fl oz/100 gal (100 – 200 ml/hl = 20 – 30 g/hl)
Must fining	6.4 – 12.8 fl oz/100 gal (50 – 100 ml/hl = 10 – 20 g/hl)
Fining of grape juice	6.4 – 12.8 fl oz/100 gal (50 – 100 ml/hl = 10 – 20 g/hl)
Wine fining	3.2 – 10.24 fl oz/100 gal (25 – 80 ml/hl = 5 – 16 g/hl)

Fining Preparation and Procedure

SIHA Gelatin Liquid fining agent is easy to measure and dose. Provided it is thoroughly mixed it can be stirred directly into the beverage.

For mash finings and in applications where mixers with inadequate effect and unfavorably shaped containers are used, e.g. rectangular tanks or concrete tanks, it should be pre-diluted with about 10 times the beverage quantity.

For mash fining the pre-diluted SIHA Gelatin Liquid fining agent can be added continuously to the mash flow. If small mash containers are used, the fining may be distributed directly on the grapes, perhaps together with the required quantity of dissolved SIHA Potassium Pyrosulphite stabilizer. Mixing is then done during grape crushing, mash pumping and filling of the press.

Before adding SIHA Gelatin Liquid fining agent to the beverage to be fined, it should be agitated with a high-performance mixer. Then slowly add the gelatin solution to the beverage.

In general, the gelatin fining will settle within one day. Flocculation can be improved and accelerated through secondary fining with BEVASIL 30 silica sol fining agent or SIHA Bentonite fining agents (all types).

Combination of fining agents

Particularly for clarification of must and young wines, we recommend combining SIHA Gelatin Liquid fining agent with negatively charged flocculation agents. The combination of SIHA Gelatin Liquid fining agent with BEVASIL 30 silica sol fining agent has been tried and tested. As a general guideline a ratio of 1:5 to 1:10 (gelatin to silica sol) is recommended. The exact ratio should be determined in a laboratory test.

Product Characteristics

SIHA Gelatin Liquid fining agent is a 20% solution. Five times the quantity of dry gelatin (cold-soluble gelatin) must therefore be used. It can be added directly to the product without any preliminary treatment.

Safety

When used as directed and handled correctly, there are no known unfavorable effects associated with this product.

Further safety information can be found in the relevant Material Safety Data Sheet, which can be downloaded from our website.

Storage

SIHA Gelatin Liquid fining agent is produced with extreme care. It is stabilized, but has only a limited shelf life. Open packages should be used up quickly. Unopened packages should be stored in a cool place.

Delivery Information

SIHA Gelatin Liquid fining agent is sold under article no. 97.101 and is available in the following package sizes:

2.2 lb (1 kg)	PE bottle
13.2 lb (6 kg)	PE canister
55.1 lb (25 kg)	PE canister
2,205 lb (1,000 kg)	one-way tank on request

HS Customs Tariff: 3824 90 97

Certified Quality

SIHA Gelatin Liquid fining agent is inspected regularly during the production process to ensure consistently high product quality. These inspections include technical functional criteria as well as safety in accordance with the relevant laws governing the production of foods. Strict controls also take place immediately before and during final packaging.

BEVASIL 30 is a registered trademark of Akzo Nobel GmbH

North America - HQ

44 Apple Street,
Tinton Falls, NJ 07724
Toll Free: 800 656-3344
(North America Only)
Voice: +1 732 212-4700

Europe/Africa/Middle East

Auf der Heide 2
53947 Nettersheim, Germany
Voice: +49 2486 809-0

Internormen Product Line

Friedensstraße 41
68804 Altlußheim, Germany
Voice: +49 6205 2094-0

Begerow Product Line

An den Nahewiesen 24
55450 Langenlonsheim, Germany
Voice: +49 6704 204-0

Brazil

Av. Julia Gaioli, 474 - Bonsucesso
07251-500 - Guarulhos
Brazil
Voice: +55 11 2465 8822

China

No. 7 Lane 280 Linhong Road,
Changning District,
Shanghai 200335, China
Voice: +86 21 5200 0422

Singapore

4 Loyang Lane #04-01/02
Singapore 508914
Voice: +65 6825 1668

For more information, please e-mail us
at filtration@eaton.com or visit us online
at eaton.com/filtration for a complete list
of Eaton's filtration products.

Not all products in Eaton's Begerow
Product Line are available in all regions.
Please contact your local Eaton
Filtration office to determine availability.

© 2013 Eaton Corporation. All Rights Reserved. All
trademarks and registered trademarks are the
property of their respective owners.

All information and recommendations appearing in
this brochure concerning the use of products
described herein are based on tests believed to be
reliable. However, it is the user's responsibility to
determine the suitability for his own use of such
products. Since the actual use by others is beyond
our control, no guarantee, expressed or implied, is
made by Eaton as to the effects of such use or the
results to be obtained. Eaton assumes no liability
arising out of the use by others of such products.
Nor is the information herein to be construed as
absolutely complete, since additional information
may be necessary or desirable when particular or
exceptional conditions or circumstances exist or
because of applicable laws or government
regulations.



Powering Business Worldwide

EN
1 B 4.2.5
08-2013